

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ENVIROTEX LITE - RESIN

PRODUCT CLASS: EPOXY RESIN

PRODUCT NUMBER: 02007, 02007C, 02008, 02008C, 02016, 02016C, 02032, 02032C, 02064, 02064C, 02128, 02128C
05080R

D.O.T. SHIPPING INFORMATION: NON-HAZARDOUS

TRANSPORTATION EMERGENCY PHONE NUMBER: CHEMTREC (800) 424-9300

SECTION I

ENVIRONMENTAL TECHNOLOGY, INC.
300 SOUTH BAY DEPOT ROAD

FIELDS LANDING, CA 95537
PHONE NUMBER FOR INFORMATION: (707) 443-9323

DATE PREPARED: 3/2/2009

PREPARED BY: TECHNICAL DEPARTMENT



SECTION II Hazardous Ingredients/Identity Information

HAZARDOUS COMPONENTS	CAS REG.NO.	APPRO X WT. %	ACGIH TWATLV	OSHA PEL	VAPOR PRESSURE mm Hg
BISPHENOL A/EPICHLOROXYDRIN RESIN	25068-38-6	85	N/S	N/E	<1
ALIPHATIC AND AROMATIC GLYCIDL ETHERS	MIXTURE	15	N/E	N/E	<1

Although no exposure standards have been established for this product, air contaminant concentrations must be maintained at lowest possible levels. T/S = TRADE SECRET N/A = NOT AVAILABLE N/E = NOT ESTABLISHED

SECTION III - Physical/Chemical Characteristics

BOILING RANGE °F	>350	PERCENT VOLATILE BY VOLUME		T/S
MELTING OR FREEZING POINT	N/A	PERCENT VOLATILE BY WEIGHT		T/S
VAPOR DENSITY (AIR=1)	>1	EVAPORATION RATE (SLOWER THAN ETHER)	LBS./GAL	9.6
SOLUBILITY IN WATER: SLIGHTLY SOLUBLE			VOC LBS/GAL	0
APPEARANCE AND ODOR: CLEAR, COLORLESS, VISCOUS LIQUID WITH CHARACTERISTIC, EPOXY RESIN ODOR			VOC GRAMS/LITER	0

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): TOC >160°F FLAMMABLE LIMITS: LEL: N/E UEL: N/E
EXTINGUISHING MEDIA: FOAM ALCOHOL FOAM CO₂ DRY CHEMICAL WATER SPRAY
OTHER
SPECIAL FIRE FIGHTING PROCEDURES: USE NIOSH APPROVED PROTECTIVE CLOTHING INCLUDING POSITIVE PRESSURE SELF CONTAINED BREATHING APPARATUS(SCBA). COOL UNOPENED CONTAINERS WITH WATER SPRAY.
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE EXPECTED

SECTION V - REACTIVITY DATA

STABILITY UNSTABLE STABLE / CONDITIONS TO AVOID:

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ENVIROTEX LITE - RESIN

Page 2 of 3

INCOMPATIBILITY (MATERIALS TO AVOID): AVOID CONTACT WITH STRONG ACIDS, AMINES OR OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: BURNING PRODUCT WILL EMIT TOXIC FUMES INCLUDING OXIDES OF CARBON AND NITROGEN, AND VARIOUS CHLORINATED COMPOUNDS.

HAZARDOUS POLYMERIZATION MAY OCCUR MAY NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION? YES SKIN? YES INGESTION? UNLIKELY

HEALTH HAZARDS (ACUTE AND CHRONIC): MILDLY IRRITATING TO EYES AND SKIN, VAPORS AND/OR SKIN CONTACT COULD CAUSE SENSITIZATION. VAPORS ARE IRRITATING TO RESPIRATORY TRACT. REACTIONS TO INGESTION ARE UNDETERMINED.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

SIGNS AND SYMPTOMS OF EXPOSURE: SENSITIZATION MAY CAUSE HIVE-LIKE RASH AND BREATHING DIFFICULTIES. EYE OR SKIN CONTACT WOULD PRODUCE REDNESS AND IRRITATION.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: PRE-EXISTING SKIN OR EYE PROBLEMS MAY BE WORSENERD BY EXPOSURE TO THIS PRODUCT. EXISTING ALLERGIES MAY INCREASE THE POSSIBILITY OF ALLERGIES TO THIS MATERIAL.

EMERGENCY AND FIRST AID PROCEDURES: **ORAL:** INDUCE VOMITING. *CALL PHYSICIAN IMMEDIATELY!* **EYES:** SEVERE IRRITANT TO EYES. IN CASE OF EYE CONTACT, FLUSH THOROUGHLY WITH WATER FOR 15 MINUTES AND *GET PROMPT MEDICAL ATTENTION.* **SKIN:** WASH IMMEDIATELY WITH SOAP AND RINSE THOROUGHLY WITH WATER. DO NOT USE SOLVENTS OR ALCOHOL TO REMOVE PRODUCT FROM SKIN. **INHALATION:** MOVE TO FRESH AIR. IF NOT BREATHING ADMINISTER CPR. IF BREATHING IS DIFFICULT GET MEDICAL ATTENTION.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: VENTILATE AREA. WEAR PROTECTIVE CLOTHING AND NIOSH APPROVED RESPIRATOR. DIKE AND CONTAIN SPILL. SPREAD ABSORBENT MATERIAL. KEEP SPECTATORS AWAY.

WASTE DISPOSAL METHOD: NOT A RCRA HAZARDOUS WASTE AS SUPPLIED; USER MUST DETERMINE RCRA STATUS AT TIME OF DISPOSAL. LANDFILL OR INCINERATE IN ACCORDANCE WITH EXISTING FEDERAL, STATE, AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE IN COOL DRY AREA, AWAY FROM STRONG OXIDANTS, HEAT OR IGNITION SOURCES. ALWAYS KEEP CONTAINERS CLOSED. DO NOT GET ON SKIN OR BREATHE VAPORS.

OTHER PRECAUTIONS: CLEAN UP ANY SPILLS IMMEDIATELY. WASH ANY AREAS OF BODY CONTACT IMMEDIATELY.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): NIOSH APPROVED TO PREVENT INHALATION OF VAPORS; IF VENTILATION IS INADEQUATE, SCBA MAY BE REQUIRED.

VENTILATION: LOCAL EXHAUST: IF REQUIRED. SPECIAL VENTILATION MUST BE ADEQUATE TO AVOID BREATHING VAPORS.

USE IN SEALED EQUIPMENT AS MUCH AS POSSIBLE. MECHANICAL (GENERAL): REQUIRED

PROTECTIVE GLOVES: NEOPRENE OR RUBBER EYE PROTECTION: SAFETY GOGGLES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: TO AVOID ALL SKIN CONTACT. WEAR PROTECTIVE APRON AND AVOID FOOT CONTACT.

WORK/HYGIENIC PRACTICES: WASH AT END OF WORK SHIFT, BEFORE EATING, SMOKING OR USING RESTROOM. DO NOT RE-USE CONTAMINATED CLOTHING.

REGULATORY INFORMATION: THIS PRODUCT IS REGULATED UNDER SARA TITLE III SECTION 311 AS ACUTELY HAZARDOUS.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ENVIROTEX LITE - RESIN

Page 3 of 3

All information, recommendations, and suggestions appearing herein concerning our product are based upon tests and data believed to be reliable. However, it is the user's responsibility to determine the safety, toxicity, and suitability for his or her own use of the product described herein. Since the actual use by others is beyond Environmental Technology, Inc.'s control, no guarantee, expressed or implied, is made by Environmental Technology, Inc. as to the effects of such use, the results to be obtained, or the safety and toxicity of the product.