

# EasyMold Silicone Putty – 33700, 33710

## Technical Bulletin

<b>General</b>	<b>EasyMold Silicone Putty is a 2-part silicone putty used for making molds.</b>
<b>Appearance</b>	<b>White/Purple (A/B)</b>
<b>Specific Gravity, 25 °C</b>	<b>1.48</b>
<b>Hardness, Shore A</b>	<b>30+ 10 -5</b>
<b>Tensile Strength [psi]</b>	<b>288</b>
<b>Elongation at Break [%]</b>	<b>208</b>
<b>Tear Strength, die B [ppi]</b>	<b>30</b>
<b>Pot Life, Minutes, Max</b>	<b>2</b>
<b>Curing Time, Minutes</b>	<b>6</b>

READ AND UNDERSTAND SAFETY DATA SHEET (SDS) FOR THIS PRODUCT BEFORE USING.

### **STORAGE:**

STORE IN TIGHTLY CLOSED CONTAINER IN A DRY, COOL AND WELL-VENTILATED PLACE. STORE AWAY FROM INCOMPATIBLE MATERIALS.

### **IMPORTANT:**

Technical information supplied by Environmental Technology, Inc. shall not constitute a representation, warranty or condition. All such advice is given and accepted at the buyer's risk. The test data and results set forth herein do not necessarily indicate the results that the buyer or user will attain. Full-scale testing and product performance is the responsibility of the buyer and user.



300 South Bay Depot Rd., Fields Landing, CA 95537  
Tel: 707-443-9323 Fax: 707-443-7962 mail@eti-usa.com