

EasyMold Silicone Rubber – 33720, 33730

Technical Bulletin

General	EasyMold Silicone Rubber is a 2-part silicone liquid rubber used for making molds.
Appearance	White/Blue (A/B)
Density Part A Part B	1.25 g/cm³ 1.26 g/ cm³
Elongation at break	550%
Hardness Shore A	20
Mix ratio	1:1
Tensile strength	4.5 N/mm²
Viscosity @ 23 °C (Part A) Viscosity @ 23 °C (Part B) Mixed Viscosity @ 23 °C	30000 cPs 30000 cPs 30000 cPs
Tear Strength	>26.3 N/mm

READ AND UNDERSTAND SAFETY DATA SHEET (SDS) FOR THIS PRODUCT BEFORE USING.

STORAGE:

STORE IN TIGHTLY CLOSED CONTAINER IN A DRY, COOL AND WELL-VENTILATED PLACE. STORE AWAY FROM INCOMPATIBLE MATERIALS.

IMPORTANT:

Technical information supplied by Environmental Technology, Inc. shall not constitute a representation, warranty or condition. All such advice is given and accepted at the buyer's risk. The test data and results set forth herein do not necessarily indicate the results that the buyer or user will attain. Full-scale testing and product performance is the responsibility of the buyer and user.



300 South Bay Depot Rd., Fields Landing, CA 95537
Tel: 707-443-9323 Fax: 707-443-7962 mail@eti-usa.com